

BioCat™

*For all your Hydrocarbon issues, from Clean-up
to Overload and discharge...*

Product Description: BioCat™

- Engineered specifically as water based, biodegradable, blended surfactant concentrate product
- Completely miscible in water and will not cloud or separate upon dilution
- **Emulsifies and encapsulates hydrocarbons; fats, oils, and grease instantly and effectively conditions (physically) the hydrocarbon such that the microbes that naturally occur can more readily consume it.**
- Increases hydrocarbon degradation and significantly reduces volatile vapors (VOC's) on initial application, with LEL's (Lower Explosive Limits) approaching "zero" in a very short time thus eliminating the potential for explosion and fire.
- Product color serves to help identify sheening for spill response
- Does not contain builders, petroleum distillates, caustics, tall oils, D-limonene, terpene, or nitrates
- Unlimited shelf life (*unopened*)

Directions: BioCat™

- To provide spill clean-up a 5% solution (16 oz. of BioCat™ concentrate to 2.5 gallons water) may be applied with a pump sprayer and scrubbed or brushed into surface.
- Floor machines use a .05% to 5% solution per gallon.
- **Waste Stream overload: a simple dosing program into you waste stream may provide the protection you where looking for, eliminating costly downtime.**
-

BioCat™ Benefits

- Affordability—effective at light concentration working dilution (i.e. 5%)
- Environmentally friendly – permanently removes the contaminant from the environment
- **Eliminates costly downtime from Hydrocarbon over load (FOG)**
- Complements storm water runoff programs
- Complements ZERO RELEASE FACILITIES
- Makes water soluble chemistries more soluble
- Upon proper application and wash down to containment, BioCat™ will instantly stop the deterioration of asphalt by diesel or gasoline and immediately eliminate slippery conditions and secondary hazards
- BioCat™ is equally effective on all types of Vehicle Operating Fluids (i.e. glycol/antifreeze, motor oil, diesel, gasoline, hydraulic oil, **synthetics...**)
- Quick, easy, and safe to use



Surfactant Technologies LLC Sheboygan, WI 53081
Ph: 920-208-8822 Fax: 920-208-8823 www.surfactanttech.com